

ARL945-B

17.3" LCD, CORE 2 DUO PROCESSOR
MULTI-SLOT PORTABLE COMPUTER



Features

- All-in-one design rugged portable computer
- Compact Size Lightweight Design
- Built-in 17.3" LCD with LED backlight , 1920x 1080
- 2x 95W Li-ion battery packs, 100W adapter
- Intel Core 2 Duo T7500 (2.2GHz) Processors
- Industrial Keyboard multi-language with touchpad
- 2 PCI full-length expansion slots
- Built-in 500GB, support 1x 2.5" removable SATA
- Dual Gigabit Ethernet, 2x COM Port
- Carrying case to manage portable PC with ease

Ordering Information

ARL945-B17WUSB

17.3" LCD, 1920x 1080, T7500 CPU, 2x 2G RAM, 500G HDD, 2 PCI slots, DVD-RW, Battery Packs, Carrying case

ARL945-B17USB

17.3" LCD, 1600x 900, T7500 CPU, 2x 2G RAM, 500G HDD, 2 PCI slots, DVD-RW, Battery Packs, Carrying case

Note: Keyboard layout: CH, FR, GR, KR, RU, SP, UK, US



Carrying Case



Air Cargo Case

Specification

| Model No | ARL945-B |
|---------------|-------------------------------------------------------------------------------------------|
| Construction | Rugged Aluminum Construction |
| CPU | Intel Core 2 Duo T7500, 2.2GHz Processors Option: Intel Core 2 Duo T9400, 2.53GHz |
| Chipset | Intel Gm45 Chipset + ICH9M |
| Slot | 2 PCI full-length expansion slots |
| Display | 17.3" LCD with LED backlight, 1920x 1080, 262K, Anti-reflection tempered strengthen glass |
| Memory | 2x 2GB RAM |
| HDD | 1x 500GB 2.5" HDD, support 1x 2.5" removable SATA |
| CDROM | 1x Slim DVD-RW |
| Interfaces | 4x USB 2.0 Ports, 1x VGA Port, 2x Gigabit LAN 2x COM port, PS2 KB/MS, Audio |
| Audio | ICH9M built-in audio HD audio w/ Realtek ALC888 |
| LAN | Dual Gigabit LAN, RJ-45 connector |
| Speaker | Built-in amplified 2x 3W speakers |
| KB/MS | 104-key industrial keyboard with touchpad |
| PSU | 2x 95W Li-ION battery Packs (Hot-Swappable) 100W, 90~264 VAC adapter |
| Dimension | 428.6x 100.5x 367.5 mm (Wx Hx D) |
| Weight | 6.8 kgs |
| Carrying Case | Padded carrying case with wheels |

Environmental Factors

| | |
|-------------------|---------------|
| Temperature | -20°C~60°C |
| Relative Humidity | 10%~90% |
| Approval | CE, FCC, RoHS |