

AMK808-VB

LCD keyboard drawer



Specification

Model No	AMK808-VB
Construction	Heavy-duty steel
Drawer design	1U, single slide rail LCD KB drawer for 19" cabinet
Display	17", 1280x 1024 resolution with tempered glass Option: 19", 1280x 1024 with tempered glass
Protection	Tempered glass protect LCD screen
Physical security	Key locking mechanism
KVM switch	8 port DVI KVM switch
LED indication	Online LED indicates a computer is connecting Select LED indicates the current operation PC port
Keyboard	Industrial keyboard with touchpad Option KB: CH, FR, GR, IT, JP, KR, PT, RU, SP, UK, US
Power supply	Built-in 60W, 90~264VAC, Operating temp.: -20~70°C
Power consumption	3 watts stand-by, 25 watts in-use
Dimension	442.4x 44x 590mm (Wx Hx D)
Weight	12 kgs
KVM cable	8x DVI cables, 8x USB cables

Environmental Factors





	Operating	Non-Operating
Temperature	0°C~50°C	-20°C~60°C
Relative Humidity	10%~90%	10%~95%
Approval	CE, FCC, RoHS	

Features

- Meets EIA310c & IEC-3 specification
- 1U, Single slide rail, 17" or 19" LCD Keyboard drawer
8 port DVI KVM switch
- Built-in 17" LCD monitor, 1280x 1024 resolution
Option: 19", 1280x 1024 LCD monitor
- Industrial keyboard with touchpad
- Includes a key-locking mechanism to prevent unauthorized access
- Built-in rail self-locking device
- Tempered glass protect LCD screen

KVM switch

- 8-port rack mountable DVI KVM, USB KB/MS
- 8x DVI-D video connectors, and 8x USB type A Female KB/MS connectors
- Support Windows, DOS, Netware, Unix, Linux, IMAC, Power MAC and Sun Micro systems with USB
- Hot plug- add or remove connected computer without powering off the KVM switch or computer
- No software required. Easy computer selection via Front push buttons, keyboard Hot Key



Ordering Information

AMK808-17VBUS

1U, 17", 1280x 1024, 8-port DVI KVM with 8x DVI/USB cables

AMK808-19VBUS

1U, 19", 1280x 1024, 8-port DVI KVM with 8x DVI/USB cables